

Diagram illustrating the layout and dimensions of a bus shelter, showing two shelter location options (Option 1 and Option 2) relative to the kerb face and property line.

Dimensions and Layout:

- Property Line:** Indicated by a horizontal line.
- Kerb Face:** Indicated by a horizontal line.
- Approach Taper:** 1 IN 6 APPROACH TAPER (MINIMUM) on the left side.
- Departure Taper:** 1 IN 2 DEPARTURE TAPER (MINIMUM) on the right side.
- Shelter Location Option 1:** Dimensions include 4100 (width), 1500 (depth), and 1000 (height).
- Shelter Location Option 2:** Dimensions include 4100 (width), 1000 (height), and 750 (SIGN) (height).
- Bus Stop Sign:** Dimensions include 2000 (width) and 10000 (NON-SIGNALISED) / 20000 (SIGNALISED) (height).
- Warning TSGI's:** (REQUIRED WHEN BUS SHELTER IS AGAINST PROPERTY BOUNDARY).
- TSGI's (DIRECTIONAL):** Dimensions include 9000 (width) and 1500 (height).
- TSGI's WARNING:** Dimensions include 4100 (width) and 1500 (height).
- R1000 CLEARANCE ZONE TO OBSTACLE:** Indicated by a curved line.
- Minimum Footpath Length:** 11000 (MINIMUM FOOTPATH LENGTH).
- Other Dimensions:** 9000, 4000, 2500, 1500, 1000, 600, 300, 300, 600, 750 (SIGN).